



# RGB PLUS Line

## 24Vdc Pebble Lights-2LED

### RGB+360Peb-24v / RGB+180Peb-24v

**Lens:** clear, frosted

**Pitch:** 4-, 6-, 12-inch, custom

**View Angle:** 360-, 180-degs.

**Bulb Count:** 5-, 10-, 25-light, custom

**Wire Color:** black, green, white, clear

**Ends:** thru-connect, terminated

Output	
LED Type	SMD5050
LED Channels	R-G-B, or R-G-B-WW option
Greyscale	16-bit, 65,536 dimming levels*
LED Quantity	2 / pixel
Viewing Angle	360-degrees (or 180-deg., option)
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC+, MC+
Max Lights before power injection	approx. 200L (to be verified)
Max Distance before Power Injection	approx. 180-feet (to be verified)
Electrical & Safety	
Input Voltage	24 VDC
Current	0.015 Amps
Power	0.36 Watts
Wire	20 AWG, 3C, UV protected
Inline power injection	via Minleon Power T+'s & RGB+4A-24v
Certifications	(c)UL listed, IP 65, CE
Physical	
Size	2.0 x 0.875 x 0.5" <sup>^</sup>
Weight	approx. 0.256 oz. per bulb
Housing	polycarbonate
Mounting bracket	yes, 2-screw hole adjustable clip, add-on
Connector Type	LLT twist-lock
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.



USA HQ  
Mechanicsburg, PA  
(717) 763-1055

[www.minleonusa.com](http://www.minleonusa.com)

\* 8-bit via DDP. <sup>^</sup>180Peb-24v size is similar to RGB+Peb12v.  
Specifications as of May 2021 and are subject to change.

