



RGB+Plus Line

4-LED Pebble Lights

RGBW+PEB-4L

Lens: clear, frosted

Pitch: 4-, 6-, 12-inch, custom

View Angle: double-sided

Bulb Count: 5-, 10-, 25-light, custom

Wire Color: black, green, white

Ends: thru-connect, terminated

| Output | |
|-------------------------------------|---|
| LED Type | SMD5050 |
| LED Channels | R-G-B-W |
| Greyscale | 16-bit, 65,536 dimming levels* |
| LED Quantity | 4 |
| Chipset | RGB+2 (4-wire; DoubleDATA line) |
| Control | |
| Individually Addressable | yes |
| Control Systems | NDB+ (ArtNet, E1.31), WEC+, MC+ |
| Max Lights before power injection | approx. 160L |
| Max Distance before Power Injection | approx. 160-feet |
| Electrical & Safety | |
| Input Voltage | 24 VDC |
| Current | 0.022 Amps |
| Power | 0.53 Watts |
| Wire | 18 AWG, 3C, UV protected |
| Inline power injection | via Power T+'s & RGB+4A-24V |
| Certifications | (c)UL listed, IP 65, CE |
| Physical | |
| Diameter | 2.0 x 0.875 x 0.5" |
| Weight | approx. 0.256 oz. per bulb |
| Housing | polycarbonate |
| Mounting bracket | yes, 2-screw hole adjustable clip, add-on |
| Connector Type | LLT twist-lock |
| Operating Temperature | Neg -20 to +50 Cel. / Neg -4 to +122 Far. |



USA HQ
Mechanicsburg, PA
(717) 763-1055

www.minleonusa.com

* 8-bit via DDP.

Specifications as of May 2021 and are subject to change.

