



# RGB+PLUS Line Faceted Mini-TrikLits RGB+Trik30F-12v

**Pitch:** 4-, 6-, 12-inch, custom

**Bulb Count:** 5-, 10-, 25-light, custom

**Wire Color:** black, green, white

**Ends:** thru-connect, terminated, eye-hole loop

| Output                              |   |
|-------------------------------------|---|
| LED Type                            | SMD5050                                   |
| LED Channels                        | R-G-B                                     |
| Greyscale                           | 16-bit, 65,536 dimming levels             |
| LED Quantity                        | 2   |
| Viewing Angle                       | 360-degrees                               |
| Control                             |   |
| Individually Addressable            | yes                                       |
| Control Systems                     | NDB+ (ArtNet...), WEC+, MeshTek BLE       |
| Max Lights before power injection   | approx. 125L                              |
| Max Distance before Power Injection | approx. 100-feet                          |
| Electrical & Safety                 |   |
| Input Voltage                       | 12 VDC                                    |
| Current                             | 0.028 Amps                                |
| Power                               | 0.336 Watts                               |
| Wire                                | 22 AWG, 3C, UV protected                  |
| Inline power injection              | via Minleon Power T+'s & RGB+5A-12V       |
| Certifications                      | (c)UL listed, IP 66                       |
| Physical                            |   |
| Diameter                            | 30mm                                      |
| Weight                              | approx. 0.04 lb.                          |
| Housing                             | polycarbonate                             |
| Bulb Style                          | faceted                                   |
| Connector Type                      | LLT twist-lock                            |
| Operating Temperature               | Neg -20 to +50 Cel. / Neg -4 to +122 Far. |



USA HQ  
Mechanicsburg, PA  
(717) 763-1055

[www.minleonusa.com](http://www.minleonusa.com)

Specifications as of Aug. 2024 and are subject to change.

