



P50H Fat Pebbles

4-wire, DoubleDATA Line

P50H-RGBW+2-PEB180

Lens: clear, frosted

Pitch/Spacing: 12", 6-inch, custom

View Angle: three-sided

Bulb Count: 1-, 2-, 5-, 10-, 25-light, custom

Wire Color: clear, black, white, sand, green

Ends: thru-connect, terminated

OUTPUT	
LED Type	SMD3535
LED Quantity	2
LED Channels	R-G-B-W (~3000K), R-G-B (option)
Protocol	UCS7604, UCS5603 (RGB option)
Chipset Settings	RGBW+2 / 4-wire
Greyscale	12-bit, 4096 dimming levels*
CONTROL	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC3+, MeshTek
POWER	
Input Voltage	24 VDC
Current	0.015 Amps*
Power	0.36 Watts*
Max Lights before power injection	approx. 200L*
Max Distance before Power Injection	approx. 220-feet*
Wire	20 AWG, 4C, UV protected, 5-Amp MAX
Connector Type	LLT twist-lock, 4-pin, 5-Amp MAX
Inline power injection	via 4-wire Power T+'s & RGB+4A-24V
PHYSICAL	
Diameter	2.5 x 0.625 x 0.875"
Weight	approx. 0.5 oz. per bulb
Housing	polycarbonate
Mounting bracket	yes, 3-foot pvc track sections Item: RM-TC03
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.
Certifications	(c)UL listed**, IP 66, CE



The P50H, 4-wire Pebble is a new, deeper version of the one Rainmin has manufactured since 2019. The P50H Pebble will extend beyond its mounting track so the LEDs are visible from three sides.



USA HQ
Mechanicsburg, PA
(717) 763-1055

www.minleonusa.com

*All specs for when using Minleon-Rainmin NDB's & WEC's. With non-Minleon controllers, power may be more than double the listed values; customers must test with their specific controllers & software to determine the maximum.

**Lights are only UL listed when using a Class 2 power supply <=4A. Specifications as of March 2025 and are subject to change.

